



International Journal of Mobile Network Design and Innovation

ISSN online: 1744-2850 - ISSN print: 1744-2869

<https://www.inderscience.com/ijmndi>

Comprehensive guide to indoor localisation: exploring wireless technologies

Sankarsan Panda, B. Bharathi, K.B. Aruna, K. PeriyarSelvam

DOI: [10.1504/IJMNDI.2025.10070022](https://doi.org/10.1504/IJMNDI.2025.10070022)

Article History:

Received:	20 December 2024
Last revised:	03 February 2025
Accepted:	24 February 2025
Published online:	16 June 2025

Comprehensive guide to indoor localisation: exploring wireless technologies

Sankarsan Panda

Acharya Shri Mahapragya Institute of Excellence (ASMIE),
Mahapragya Nagar, Asind, Bhilwara,
Rajasthan, 311301, India
Email: pandasankarsanasind@gmail.com

B. Bharathi*

Department of Artificial Intelligence and Data Science,
V.S.B. Engineering College, Karur,
NH-67, Covai Road, Karudayampalayam Post,
Karur, 639111, Tamil Nadu, India
Email: bharathi202@outlook.com
*Corresponding author

K.B. Aruna

Department of Computer Science and Engineering,
S.A. Engineering College,
Poonamallee-Avadi Main Road,
Thiruverkadu, Chennai, Tamil Nadu, 600077, India
Email: arunakb@saec.ac.in

K. PeriyarSelvam

GRT Institute of Engineering and Technology,
GRT Mahalakshmi Nagar,
Chennai-Tirupathi Highway, Tiruttani,
Tiruvallur District, 631209, Tamil Nadu, India
Email: drperiyarselvam@gmail.com

Abstract: It's getting more and more important in school and business to be able to find your way around inside buildings as network technology and smart phones become more common. Wi-Fi technology has a lot of potential for use because it is widely available in general open spaces. The majority of the currently available methods of predicting locations based on a collection of annotated Wi-Fi observations make use of trilateration or machine learning techniques. In order to instruct the models, a mixed learning strategy must be developed. This approach combines controlled, unsupervised, and semi – supervised learning methodologies to maximise the value of the gathered data. Extensive trials indicate that our method allows the models to acquire useful information from unlabelled data with gradual gains. Furthermore, it has the potential to achieve impressive performance in terms of localisation and navigation in an indoor environment that is complicated and contains obstacles.

Keywords: indoor localisation; wireless technology; decode model for indoor localisation; indoor navigation task; HPO; hyperparameter optimisation.

Reference to this paper should be made as follows: Panda, S., Bharathi, B., Aruna, K.B. and PeriyarSelvam, K. (2025) 'Comprehensive guide to indoor localisation: exploring wireless technologies', *Int. J. Mobile Network Design and Innovation*, Vol. 11, No. 3, pp.143–151.

Biographical notes: Sankarsan Panda is an Associate Professor at Acharya Shri Mahapragya Institute of Excellence at Asind and received his PhD from Sangam University, Bhilwara in Computer Science and Engineering. He is awarded MCA from Jaipur National University, Jaipur and BTech (CS) from JRN Rajasthan Vidyapeeth University, Udaipur. He had attended international and national conferences, seminars, workshops, webinars and FDP. He has published four research papers in some reputed journal such as UGC Care, Scopus and IEEE. He is keenly interested in artificial intelligence and machine learning, coding and teaching. He is astonished and influenced from the power of computing. His goal is to combine diverse range of

experiences with the ability to be an innovative academician and administrator who will contribute favourably to the concerned institute, society and research communities as well as be caring, energetic, intellectual and creative.

B. Bharathi has completed her MTech in Information Technology from Bharathidasan University, Trichy and currently working as an Assistant Professor in the Department of Artificial Intelligence and Data Science (AI&DS) at V.S.B. Engineering College, Karur, Tamil Nadu, India. She has completed her Bachelor of Technology in Information Technology from Institute of road and transport technology, Erode. She has six years three months of teaching experience and has attended many FDP, online courses like Udemy, Coursera and conferences. Her area of research interest includes machine learning, artificial intelligence, computer networks and DBMS.

K.B. Aruna received her BE, ME degrees from Anna University, Chennai, India. She has 10+ years of teaching experience and currently working as Assistant Professor in the Department of Computer Science and Engineering, S.A. Engineering College, Chennai, India. Her research interests include cloud computing, machine learning, IoT and deep learning.

K. PeriyarSelvam received her DECE, BE (ECE) and ME in Applied Electronics in 2001, 2004 and 2011, respectively. She received her Doctoral degree in 2021. She is having around 18 years of teaching experience and presently working in GRT Institute of Engineering and Technology, Tiruttani. She has published more than 20 papers in international journal/conferences. She is a reviewer in the MAT journals (*Journal of Analog and Digital Communications*, and *Journal of Embedded Systems and Processing*). Her area of interest is sensors, signal processing, analogue and digital communication.

1 Introduction

One of the primary objectives of the next Sixth Generation (6G) communications has been suggested to be achieving indoor localisation with an accuracy of less than 10 cm (Yassin et al., 2017). Given that it has the ability to spark both the current and the next industrial revolution, this makes logical. Indoor localisation finds usage in several applications like as tracking and asset management in warehouses, self-governing robot navigation, patient monitoring in assisted living facilities and numerous others (Laoudias et al., 2018). Measurements from certain fixed landmarks are taken in order to localise, or locate, a target device. The collection of markers that the localisation system uses is called a map. The global positioning system (GPS), which determines receiver positions using satellites, has long been advised for outdoor localisation. This has been the recognised approach to localisation. Unfortunately, GPS signals are not suitable for interior localisation since they cannot pass through building roofs and walls. Furthermore, the inside situation is considerably more challenging than the outside scenario because to the increased multipath issues caused by many reflections and barriers that block the direct line-of-sight (LoS) contact between the transmitter and the receiver. Simultaneous localisation and mapping, or SLAM for short, is closely connected to the idea of localisation as it builds the map at run-time using measurements from the device that is designated as the target (Aslan et al., 2021). This has the benefit of not requiring the application to have the details of the map coded into it. For applications meant for practical use, considerations including scalability, cost, setup, and recurring expenditures must be made while choosing an installation method for translation.

Indoor location has been the focus of research on a number of technologies, including as Bluetooth low energy (BLE), ultra-wide band (UWB), inertial measurement unit (IMU), and Wireless Fidelity (Wi-Fi). This is owing to the fact that these technologies are readily available in current cellphones, which has led to their widespread adoption in modern homes and workplaces. Consequently, the unit cost of such gadgets has decreased as a result of their increased availability. Due to this particular reason, they have been selected as the target population for this study. There are a lot of reasons why other technologies that are either included in a contemporary smartphone or that are accessible at a reasonable cost have not been regarded as the primary goals of this investigation. Every one of these technologies that have been described has both positives and negatives associated with it. The Data Fusion (DF) approach is often utilised in order to maximise benefits while simultaneously minimising drawbacks. It has been shown that DF is a common approach in the area of indoor positioning (Haque et al., 2019). DF has been used in a broad variety of domains.

1.1 Related work

During the last 10 years, indoor localisation has been a subject of study that has been actively pursued, and there are several surveys that are accessible on this subject. The technology and methods that are accessible on smartphones are the primary focus of the studies written. This specific study route is extremely comparable to the one that was pursued in the work that is now being discussed. However, with the advent of new technologies like BLE AoA determination and UWB integration in modern smartphones (He and Chan, 2015), the 2017 study by Davidson and

Piché is no longer valid. Moreover, Naser et al. omitted to include UWB into their investigation and failed to assess the accuracy they were able to get across different technologies in the literature. The authors of examined many wireless indoor localisation techniques. Among these technologies are WiFi, FM radio, and long-range broadband-area networks (LoRaWAN). None of them took advantage of the widely accepted method of indoor localisation by inertial methods, which is made possible by the low-cost equipment needed. The restricted their discussion to inertial IPS and concentrated only on this specific approach. The efficacy of an inertial intrusion prevention system (IPS) is increased, according to the paper, when it is integrated with another IPS that uses a different technology. A thorough analysis of this specific DF method was published in Harle (2013). The authors of the research looked at a range of technologies and how they were combined. Three categories exist for data fusion: homogeneous (describing a system based on a single technology and one or more measurement types), hybrid (referring to the combination of multiple technologies and measurements), and heterogeneous (describing the use of multiple technology types with a single measurement type, such as RSS). The latter includes using an inertial IPS in conjunction with other technologies. WiFi and inertial were determined to have the most stated mentions of any pairing (Harle, 2013). The authors also discussed the potential use of machine learning (ML) to address the dilemma of decision-making.

A number of studies have been done over the years that have been about ML. The writers of looked into a lot of different machine learning (ML) use cases and methods. They also made comparisons between systems that did and did not have ML. They gave a full study of the problems with the methods currently used in the papers, along with possible ways to fix these problems. In their study of machine learning, writers focused on WiFi RSS tracking, which is a very narrow field. In addition, they gave an in-depth summary of the machine learning techniques utilised in RSS tracking. The writers of looked at machine learning methods for indoor location and paid special attention to SLAM, which stands for simultaneous localisation and mapping. The second paper was about visual SLAM, which had many important parts like loop closure, optical flow, Visual Odometry (VO), and more. Although the first one and the second one both looked at the same SLAM areas, we wanted to add direct performance measures to their evaluations of the methods.

1.2 Motivation and contribution

Our selection of the technologies that were examined is supported by the rationale that is presented in the next section.

An in-depth investigation of the technologies that are used for indoor localisation was carried out, with a specific focus on the degree to which the technology is suitable for installation.

It's important to be aware of the boundaries of current methods for indoor localisation and to think about what other areas of study might be possible in the future.

1.3 Outline of paper

The remainder of this work is divided into the following sections. Section 2 offers a comprehensive overview, highlighting the many methods that may be used in conjunction with an indoor positioning system (IPS) and providing performance statistics from the relevant literature. At the conclusion of this part, a comparison is made between the various technologies that have been discussed in detail with relation to important performance criteria.

2 Related work

There are a lot of papers that examine the various approaches to indoor placement and compare and contrast different tactics. Angulation, scene analysis, and closeness are some of the indoor localisation algorithms that were examined by Liu et al. (2007). In addition to this, their study investigates performance parameters such as accuracy, precision, complexity, resilience, scalability, and cost. It is being examined to implement technological solutions such as GPS, radio-frequency identification (RFID), wireless local area network (WLAN), Bluetooth, UWB, and cellular, among others.

Within the scope of their comprehensive investigation of wireless indoor localisation methods, the authors of Amjad et al. (2023) investigated a variety of strategies from the perspective of the device concerned. In their analysis, the scientists compared systems that were reliant on a particular device vs. those that were independent of that device, taking into account aspects such as precision, cost, scalability, and energy efficiency.

The Wi-Fi fingerprinting technique was investigated by Xiao et al. (2016) with a particular emphasis placed on two essential aspects: advanced location methods and successful technology implementation tactics. During the course of the research, a variety of methods that make use of spatial and temporal signal patterns were investigated. Accessibility to interior places, supplemental data for position estimation, as well as constraints and claimed average accuracy, were some of the specific aspects that were taken into account.

Researchers Hassan et al. (2015) looked at the use of visible LED light technology for interior placement. They looked at a variety of technologies, including as GSM, BLE, and Wi-Fi, with a focus on cost, complexity, accuracy, resilience, and the ability to reuse several infrastructures. It was also evaluated by Latif et al. (2022) that the effectiveness of several localisation techniques was evaluated.

Gu et al. (2009) also looked at a number of indoor location methods, with a focus on mobile WiFi networks. In their in-depth study, they looked at a lot of different choices, some of which were for business and some were

for research. The options were picked based on factors such as cost, speed, reliability, complexity, user preferences, business access, and restrictions. They found the same thing that other studies had found: each answer is made with a different technology, works best in certain situations, and is built in a certain way.

In their study Tiglaio et al. (2021) presented a complete review of the various smartphone-based indoor localisation algorithms that are currently used. For the purpose of classifying the methods, a classification system is offered, and the conclusion that was reached is that every approach has its own set of advantages and disadvantages. An observation was noted that route loss prediction methods provide a high degree of accuracy in some scenarios, but fingerprinting approaches work extremely well when the training step is executed effectively. Based on what the person wants, the right method is picked. In the long term, the researchers want to make an indoor localisation system that works smoothly, uses little power, and is accurate down to the centimetre level.

Liu et al. (2003) have proposed an accurate and low-cost real-time interior locating approach using Pedestrian Dead Reckoning (PDR) and iBeacons. In addition, this work introduces a PDR and iBeacon fusion approach to address location jumps and drifting issues. Furthermore, the research proposes a heading direction filtering-based PDR method. Real-time tracking tests were used to determine that starting position errors and orientation disturbances had less of an impact and that the trajectory's accuracy had increased.

By creating a customised iBeacon protocol that was specifically adapted to the problem, Conte et al. (2014) showed the utilisation of BLE for the purpose of addressing occupancy detection. Their technology, which they name BLUESENTINEL, offers an easy and scalable solution for occupancy detection. It does this by using the current cellphones of users in conjunction with beacons that are strategically placed. The results of their trials shown that it is possible to acquire precise findings with a single beacon in each room, which is in contrast to other systems that need a greater number of antennas. The BLE protocol's built-in power efficiency offers further proof that their plan is workable. The accuracy achieved by BLUESENTINEL is equivalent to that of more complex approaches, despite the fact that it is fairly simple.

Zone-level occupant localisation was made possible via a non-intrusive BLE-based method that did away with the need for a specialised mobile application. Then, these are turned into RSSI tuples, which are then used by guided or semi-supervised machine learning methods to find out where the people living in the zones are. The semi-supervised grouping method worked well with less training data and work, while the supervised ensemble model was more accurate and had a higher f1-score. Furthermore, the supervised ensemble model had higher accuracy. This strategy worked well, as shown by a case study done in an office context. As a consequence, occupancy profiles were created, which provide valuable details about the activities

of tenants. Facility managers may get important insights about occupancy levels by using this recommended strategy, which is essential for efficient building management.

An extensive examination of indoor localisation systems was presented by Andà et al. (2021). This system uses wireless ultrasonic sensors to identify the user's location in conjunction with an environmental map to allow features related to user-environment interaction. The goal of the technology is to enable safe and efficient movement of people in interior spaces. Using the Multi-Trilateration Algorithm (MTA), the RESIMA system proved to be appropriate for the application area that was being discussed. The deployment challenges related to wireless sensor networks (WSNs) were examined in detail. Since sensor nodes are dispersed and must continue to function in order to collect and disseminate data, optimising node dispersion was essential for smart cities. An analysis of the work that had already been done in the area was carried out, and coverage approaches were classified into several methods. This document discusses the research efforts that have been made to reduce the number of deployed nodes in order to minimise the amount of power that is used. This paper presents a full comparison of different methods, taking into consideration the benefits and downsides associated with each of them individually.

Obeidat et al. (2021) provide a detailed review of the methods and technologies that include wireless technology and indoor localisation techniques. There are many different technologies that are included in the survey that pertain to localisation systems. These technologies include satellite-based navigation, inertial navigation systems, magnetic-based navigation, sound-based technologies, optical-based technologies, and radio frequency (RF)-based technologies. Various techniques for object localisation are also investigated, including dead reckoning, scene analysis, proximity-based techniques, and triangulation. The most popular approaches and strategies for translation are also covered in this section. The capacity of a strategy to give great accuracy while using a minimum amount of processing resources is ultimately what determines which approaches are the most powerful. The researchers Sadowski et al. (2020) did a thorough study in which they compared how well the Trilateration, K-Nearest Neighbour (KNN), and Naive Bayes methods worked. Technology from the Internet of Things (IoT), such as Zigbee, BLE, and Wi-Fi, were used in the study. The tests used three datasets from the real world. Each one showed a different kind of room with a different amount of noise. KNN with a parameter value of $k=4$ was the most precise and ideal localisation technique. It beat out Naive Bayes by a point. KNN turned out to be the most precise and correct method.

A selection of these linked works is summarised in the table that may be seen below (Table 1).

Our study aims to investigate several indoor location methods using wireless signal technologies. Unlike other research, our paper uses analytical techniques and

simulations. The Grid-Based RSS method, the Trilateration algorithm, and the Centroid algorithm are some of the techniques under investigation. The following factors were used to judge these systems: how well they worked, how accurate they were, how well they blocked noise, how much memory they used, and how well they could change to different technology situations.

Simulations took into account the degrees of noise, the different forms of technology (Wi-Fi, ZigBee, and BLE), and the location of tag nodes. The findings of the study provide a full knowledge of the benefits and drawbacks associated with each technique, while also highlighting the relevance of addressing particular application requirements such as the amount of noise, the positioning of tag nodes, the kind of technology, and the volume of the dataset. In order to facilitate the optimisation of calibration methods and the enhancement of accuracy, all calculations were carried out using the cloud-based GPU platform Google Colab. Our results support the process of choosing workable indoor localisation solutions by offering helpful insights into the capabilities and limits of these three approaches under various conditions.

Table 1 A selection of the referenced works is summarised in the table below

Ref. no.	Localisation techniques used	Wireless technology used	Experimental settings	Parameter settings Tag placement/ scalability
Latif et al. (2022)	PF-DOA, Weighted centroid, Markov Grid, Differential RSS	Wi-Fi, ZigBee and BLE	Simulation and two real-world datasets	Consider noise but not dimension; Random, boundary and diagonal tag placement
Tiglao (2021)	Weighted centroid (range-based), Proximity-based (range-free)	Wi-Fi, ZigBee, and Bluetooth	iMinds testbed/2 real-world environment	Consider tag placement and dimension
Liu and Li (2003)	Trilateration, Fingerprinting	BLE	Real-time positioning experiments	Consider boundary tag placement
Conte, (2014)	BLE-based iBeacon	BLE	A real environment with a prototype system	Consider tag placement but not dimension
Andò et al. (2021)	Machine Learning	BLE	Two real-world datasets (2 different office areas with 650 m ² and 248 m ²) divided into zones	Occupancy density in irregular zones. Larger zones include more beacons to ensure signal coverage, with a total of 39 beacons

The key contributions of this paper can be outlined as follows:

- An examination of the many indoor localisation techniques, such as the Centroid algorithm, the Grid-Based RSS technique, and the Trilateration algorithm. Evaluating their effectiveness in various wireless situations, adjusting for route loss, and adjusting for setting dimensions.
- Simulations that were exhaustive and meticulous were carried out under a variety of experimental conditions. A comprehensive analysis of the performance of each approach was carried out, with characteristics such as efficiency, accuracy, and adaptability across a variety of technological situations being taken into consideration.
- A comprehensive investigation of the parameters that have an impact on the effectiveness of each localisation approach, including noise levels, the kinds of technologies (Wi-Fi, ZigBee, and BLE), as well as tag node density and architecture is required.

In order to optimise calibration methods and provide insights into the selection of acceptable indoor localisation approaches, the execution was carried out utilising the cloud-based GPU platform that Google Colab provides.

3 Methodology

The purpose of this part is to present a full explanation of our approach, which includes two deep models for the tasks of indoor localisation and navigation, as well as a hybrid learning strategy for the deep models that have limited data resources. This section will attempt to offer a comprehensive description of the technique that we adhere to.

3.1 Deep encode–decode model for indoor localisation task

The majority of our models, as shown in Figure 1, are built on a traditional neural network known as the variational autoencoder (VAE). The encoder and the decoder are the two main parts of the VAE network. The VAE network is made up of these two parts. Due to the fact that it incorporates explicit regularisation into the latent space, this design has the potential to make the reconstruction more resilient than the conventional autoencoder. This is because it prevents the possibility of overfitting occurring during the generating process.

The VAE network with links that are tightly joined is called ‘DF-VAE’. The ResNet design gave rise to this idea. Just to be clear, we start by making a decoder with 32, 64, 64, and 2 output channels. It has four layers that are all linked to each other. The encoder builds different levels of intermediate models from either the state data or the RSSI data. The next thing to do is to build a symmetric decoder whose layers are connected to the encoder’s layers. As the

decoding process goes on, each layer has to add the encoder's similar output to the current output channel by

channel. This is completed at each stage. It also improves the gradient flow and trains a deeper network in the process.

Figure 1 DF-VAE for reconstruction learning and DED-LM and DED-AM for location categorisation and action choice (see online version for colours)





Figure 2 Indoor navigation (a) and deep reinforcement learning (b) (see online version for colours)



3.2 Deep reinforcement learning model for indoor navigation task

We show the process of indoor travel as a Markov decision process (MDP) when we have an example that takes place inside, as shown in Figure 2. This is a statistical system used to show decision-making at the decision-making level when the results are uncertain and can be changed by the actions of the person making the decision. The MDP is made up of different states, actions that can be taken, a reward function that gives each state-activity pair a number value, and a state transition function that tells you how likely it is that an action will change the MDP from one state to another.

We provide a deep reinforcement learning model based on the MDP architecture in the work we have put together. DED-AM, or the deep encode-decode action model, is intended to be included into an agent. It is composed of a DF-VAE network and two further completely connected layers with four and 64 output channels, respectively. The process starts when the agent receives the current state data, which includes the target's distance, position coordinate (row and column numbers), and RSSI. This data will then be used to create a four-dimensional score vector, which will allow the user to choose whether to go left, right, forward, or back. Based on the completed task, the learning environment obtains the next state and reward value,

respectively, by using the reward and state transition functions in the subsequent step. Throughout this process, the DED-AM model may be trained to choose the action that consistently results in the highest reward. This will provide the optimum path from a beginning point to the desired end point.

3.3 Hybrid learning approach for deep models with limited data

The learning method is split into four parts so that different deep models can be made from the data that is provided.

To train the DF-VAE model, we first utilise all of the RSSI data, tagged or not. Now, by reassembling the input data, we want to use unsupervised learning to get feature models that are not task-specific. The repair loss is computed using the following method.

The learned weights from the DF-VAE model are used to set up the DED-LM model in the second step. Next, we use the semi-supervised learning method to gradually increase these weights on the RSSI data that has not been labelled. For more specifics, we begin by using the labelled data to train a crude DED-LM model. Next, we use the training model to label the unnamed data with high-quality labels by setting a score level that can be changed. Because of this, we can get the effects we want. This is how the localisation loss measure is defined:

$$L_{DED-LM} = -\sum_{k=1}^K y_k \log(p_k) \quad (1)$$

The number C shows a pre-generated label, also known as a ground-truth label, for the kth row or column. It has a value of 1 if the sample is collected there and a value of 0 otherwise. The predicted chance, shown by the letter P, is

what you get when you apply the softmax function to the model's output.

4 Experimental setup and results

Due to its changing nature in unpredictable settings with space-time constraints, as explained in, RSS is hard to calculate. In an effort to overcome this issue, a DT case study employs trial RSS data gathered from real circumstances in order to test the suggested CPS technique. For the purpose of determining both and, it is a standard practice to conduct experiments.


$$P_i(dB) = P_t(dB) + 10 \log_{10} K - 10 \gamma \log_{10} \left(\frac{d}{d_0} \right) - \phi(dB) \quad (2)$$

4.1 Data collection

The research is dependent on the WLAN communication infrastructure that is already present within the building. This infrastructure dictates the fixed number of access points (APs) and their location throughout the facility.

Through the use of an interactive RP generator, the quantity of RPs and their location are determined on an individual basis for each area, and this applies to both the training and tested phases. It is necessary to freeze the outer markers and waypoints before beginning the process of data collecting in order to prevent any meddling from humans. Some of these RPs have been positioned in such a way that they take into account the presence of walls and other barriers that may make it difficult to navigate specific locations. The distance between each RP is established at 0.9 m, and the number of RPs is dispersed in accordance with this distance. The corresponding results are presented in Figure 3.

Figure 3 The map of experimental areas and measurement sites (Karakusak et al., 2023) with white arrows depicts training (a–c) and testing (d–f) reference point placements and orientations (see online version for colours)



Consequently, equation (6) shows that the fingerprint matrix $F(pp)$ may be expressed mathematically by considering the d APs and n number of RSS samples received at the i th RP.

$$\mathbf{F}_{raw} = \mathbf{F}(\mathbf{p}_t) = \begin{bmatrix} r_{SS_1^1} & r_{SS_1^2} & \dots & r_{SS_1^d} \\ \vdots & \vdots & \ddots & \vdots \\ r_{SS_n^1} & r_{SS_n^2} & \dots & r_{SS_n^d} \end{bmatrix}, \mathbf{p}_t = [p_x \ p_y]^T \quad (3)$$

An RSS sampling is performed at each point while the subject is moving, and the sample rate is set at one sample per second. The characteristics of the RP planner and the number of APs that were observed are shown in Table 2, which also includes the number of train and test points that are located in each region.

4.2 Data preparation

However, these qualities often cause issues in interior environments. When signals travel over many paths, multipath fading occurs due to transmission, reflection, and diffraction off of distinct surfaces. This is the result of the signals taking many different routes. Factors such as ambient changes or human movement may also result in shadow fading and path loss situations. Both of these circumstances may manifest at the same time. These discrepancies may reduce the accuracy of placement as the location estimators construct their image of the surroundings using the radio map. This is done so that the location estimators may be told where they are by the radio map.

4.3 Experimental evaluation

It's easier to understand because the RMSE loss function uses the same unit of measurement as the real places and gives a number to the standard deviation of forecast errors. This makes it easy to see how big the error is compared to the given position unit, which is given in meters.

4.4 Hyperparameter optimisation (HPO)

The procedure of tweaking hyperparameter values, which is shown in Table 2, is an essential step in the process of developing deep learning models that are both effective and accurate. It is common for this procedure to be empirical, and it is dependent on the particular qualities of the dataset that is being entered.

Table 2 MLP, LSTM model 1, model 2, and cross-validated grid search hyperparameters

Hyperparameters	MLP	LSTM Model 1	LSTM Model 2
lag_size	–	3	3
hidden_layer	5	2	2
memory_unit	42	130	130
batch_size	27	6	130
epochs	60	40	40

The cross-validation splitting method is used in this method to look at all the possible setups by trying all the different hyperparameter pairs as a whole. Ten times through the algorithms of interest, a set of real-world tests were conducted. This was done so that the random nature of the learning methods could be taken into account. When the factors for each case were chosen, both the mean number and the standard deviation were taken into account. It was decided to use the values that gave the lowest RMSE. It also has the best hyperparameter values that were found.

5 Discussion and conclusions

Why do we need to study this? In order to learn how and what parts of a cyber-physical wireless home tracking gadget do their job. A cognitive digital twin has five traits that this design makes sure it meets. This design is different from other studies in that way. It is talked about in Section 3.1 how to grow, know what's going on around it, not need people too much, get information quickly and properly, and have a good network for talking to each other. Table 3 makes this clear.

Table 3 Comparing problem statements and experimental results

Problem statements	Assessments of results
1. Scalability: The system should be adaptable enough to function in challenging remote environments as well as a range of inside ones.	1. The system may be expanded to generate radio maps for fingerprinting-based methods by using self-governing mobile data collectors guided by a digital twin. Even though just one mobile robot is considered, the approach may be adjusted to support fleets of many robots, making it suitable for large interior spaces with multiple floors.
2. Situational Awareness: To help people make better judgements, the technology should enhance situational awareness.	2. To increase human cooperation and foster a better knowledge of interior surroundings, the system offers a graphical user interface and a synchronised 3D digital twin environment.
3. Reduce the need for human presence: To reduce labour costs associated with data gathering and to enhance facility and staff safety, the system should reduce the need for human presence in the field.	3. The technology has reduced manpower costs associated with data collection by replacing human effort with autonomous Wi-Fi site surveying. This lessens the physical effort required for data collection and maintenance, improving human safety in hazardous circumstances.
4. Reliable and effective data collecting: For more precise positioning techniques, the system should provide reliable ground-truth data collection.	4. More accurate and efficient data collection was achieved by using the SLAM algorithm and interactive reference point decision-making for Wi-Fi site surveys.
5. Effective communication network: The system must have a reasonable update latency in order to provide timely and useful information for the smooth integration of digital and physical places.	5. Software tools and digitalisation are implemented using a de facto standard ROS architecture. Its networked software communication architectures aid in the coordination of an indoor positioning ecosystem that is both cyber-physical.

The graphical user interface and synchronised three-dimensional digital twin environment both contributed to an increase in situational awareness, which in turn enabled human operators to make more information –based decisions. The method reduced the amount of money spent on labour costs while simultaneously raising safety standards by using autonomous Wi-Fi site surveying to lessen reliance on human intervention.

The purpose of this method is to lessen the bad effects of changes in RSS over time that are caused by factors in the surroundings. It could also make operations that happen from afar safer and more effective, especially in places where regular fingerprinting methods might not work or be possible, like in dangerous or faraway areas. The technology can give workers accurate information about their location without them having to go to the building in person. This is especially helpful in nuclear plants where people are not allowed to go or it's risky to do so.

Through the use of a graphical user interface and a digital twin, they are able to assume control of the robot and aid it in moving itself through the process of teleoperation. The robot will be able to restart its mission to gather the remaining fingerprint sites after it has been moved. These approaches may be used in situations when there is no human observer present.

The probable insufficiency of the suggested CPS design in terms of handling the robustness of the communication network and the restrictions of computing resources in a variety of contexts is one of the limitations of the design. It is possible that this may lead to unforeseen difficulties, problems with dependability, and performance concerns during the installation of the system. There are a few different approaches that may be used in order to overcome these constraints. These techniques can be combined with data reduction techniques or edge computing to reduce bandwidth usage and enhance system stability.

The physical environment pertaining to wireless coverage may alter as a consequence of these well-informed decisions on channel design. These improvements can include the ability to identify locations with fluctuating Wi-Fi signal strengths, dead zones, and sources of interference. These insights may then be used with the adaptive decision-making process to choose RPs and APs that are used around an area of interest in order to reduce positioning error.

References

- Amjad, B., Ahmed, Q.Z., Lazaridis, P.I., Hafeez, M., Khan, F.A. and Zaharis, Z.D. (2023) 'Radio SLAM: a review on radio-based simultaneous localization and mapping', *IEEE Access*, Vol. 11, pp.9260–9278.
- Andò, B., Baglio, S., Crispino, R. and Marletta, V. (2021) 'An introduction to indoor localization techniques. case of study: a multi-trilateration-based localization system with user–environment interaction feature', *Appl. Sci.*, Vol. 11, p.7392.
- Aslan, M.F., Durdu, A., Yusefi, A., Sabanci, K. and Sungur, C. (2021) *A Tutorial: Mobile Robotics, SLAM, Bayesian Filter, Keyframe Bundle Adjustment and ROS Applications*, Springer, Berlin/Heidelberg, Germany, pp.227–269.
- Conte, G., De Marchi, M., Nacci, A.A., Rana, V. and Sciuto, D. (2014) 'BlueSentinel: A first approach using iBeacon for an energy efficient occupancy detection system', *Proceedings of the BuildSys 2014-1st ACM Conference on Embedded Systems for Energy-Efficient Buildings*, Association for Computing Machinery, 5–6 November, Memphis, TN, USA, pp.11–19.
- Gu, Y., Lo, A. and Niemegeers, I. (2009) 'A survey of indoor positioning systems for wireless personal networks', *IEEE Commun. Surv. Tutor.*, Vol. 11, pp.13–32.
- Haque, F., Dehghanian, V., Fapojuwo, A.O. and Nielsen, J. (2019) 'A sensor fusion-based framework for floor localization', *IEEE Sens. J.*, Vol. 19, pp.623–631.
- Harle, R. (2013) 'A survey of indoor inertial positioning systems for pedestrians', *IEEE Commun. Surv. Tutor.*, Vol. 15, pp.1281–1293.
- Hassan, N.U., Naeem, A., Pasha, M.A., Jadoon, T. and Yuen, C. (2015) 'Indoor positioning using visible LED lights', *ACM Comput. Surv.*, Vol. 48, pp.1–32.
- He, S. and Chan, S.H. (2015) 'Wi-Fi fingerprint-based indoor positioning: Recent advances and comparisons', *IEEE Communications Surveys & Tutorials*, Vol. 18, No. 1, August, pp.466–490.
- Karakusak, M.Z., Kivrak, H., Watson, S. and Ozdemir, M.K. (2023) 'Cyber-WISE: a cyber-physical deep wireless indoor positioning system and digital twin approach', *Sensors*, Vol. 23, No. 24, p.9903.
- Laoudias, C., Moreira, A., Kim, S., Lee, S., Wirola, L. and Fischione, C. (2018) 'A survey of enabling technologies for network localization, tracking, and navigation', *IEEE Commun. Surv. Tutor.*, Vol. 20, pp.3607–3644.
- Latif, E. and Parasuraman, R. (2022) *Online Indoor Localization Using DOA of Wireless Signals*, arXiv 2022, arXiv: 2201.05105.
- Liu, H., Darabi, H., Banerjee, P. and Liu, J. (2007) 'Survey of Wireless Indoor Positioning Techniques, and systems', *IEEE Trans. Syst. Man Cybern. Part C (Appl. Rev.)*, Vol. 37, pp.1067–1080.
- Liu, L., Li, B., Yang, L. and Liu, T. (2003) 'Real-time indoor positioning approach using iBeacons and smartphone sensors', *Appl. Sci.*, Vol. 10, p.2003.
- Obeidat, H., Shuaib, W., Obeidat, O. and Abd-Alhameed, R.A. (2021) 'Review of indoor localization techniques, and wireless technologies', *Wirel. Pers. Commun.*, Vol. 119, pp.289–327.
- Sadowski, S., Spachos, P. and Plataniotis, K.N. (2020) 'Memoryless techniques, and wireless technologies for indoor localization with the Internet of things', *IEEE Internet Things J.*, Vol. 7, pp.10996–11005.
- Tiglao, N.M., Alipio, M., Cruz, R.D., Bokhari, F., Rauf, S. and Khan, S.A. (2021) 'Smartphone-based indoor localization techniques: State-of-the-art and classification', *Measurement*, Vol. 179, p.109349.
- Xiao, J., Zhou, Z., Yi, Y., Ni, L.M. (2016) 'A survey on wireless indoor localization from the device perspective', *ACM Comput. Surv.*, Vol. 49, pp.1–31.
- Yassin, A., Nasser, Y., Awad, M., Al-Dubai, A., Liu, R., Yuen, C., Raulefs, R. and Aboutanios, E. (2017) 'Recent advances in indoor localization: a survey on theoretical approaches and applications', *IEEE Commun. Surv. Tutor.*, Vol. 19, pp.1327–1346.